

Patent claims:

1. An electromechanical sub-assembly (1) with
5 a control module (2) equipped with first contacts (2.1),
a mechanical module (4) equipped with second contacts (4.1),
10 a support module (3) for fixing the control module (2) and
the mechanical module (4), wherein the support module (3)
comprises
first terminals (3.1) for contacting the first contacts
15 (2.1),
second terminals (3.2) for contacting the second contacts
(4.1) and
20 at least one connection device (3.3) for contacting the
electromechanical sub-assembly (1).
2. An electromechanical sub-assembly according to claim 1,
characterized in that the support module (3) contains an
25 electrically non-conducting material.
3. An electromechanical sub-assembly according to one of the
preceding claims, characterized in that the support
30 module (3) contains pressed screens (3.4) for electrical
connection of the at least one connection device (3.3), the
first terminals (2.1) and the second terminals (4.1).
4. An electromechanical sub-assembly according to one of the
35 preceding claims, characterized in that the

electromechanical sub-assembly (1) containing the control module (2), the mechanical module (4) and the support module (3) comprises an approximate cuboidal structural form equipped with corner regions.

5

5. An electromechanical sub-assembly according to claim 4, characterized in that in the corner regions of the electromechanical sub-assembly (1) at least four recesses are placed, wherein two recesses are embodied as a screwing
10 hole (9.1) for connecting the control module (2), the mechanical module (3) and the support module (3) and wherein at least two other recesses are embodied as a fixing hole (9.2) for fixing the electromechanical sub-assembly (1).

15

6. An electromechanical sub-assembly according to one of the preceding claims, characterized in that the support module (2) contains a thermal conductive, metalliferous material, and that a circuit arrangement (2.2) comprising
20 the first contacts (2.1) is mounted onto this material.

7. An electromechanical sub-assembly according to one of the preceding claims, characterized in that the control module (2) comprises a lid for covering the
25 electromechanical sub-assembly.

8. An electromechanical sub-assembly according to one of the preceding claims, characterized in that in the mechanical module (4) a plurality of actors (6) and sensors
30 (5) forming a closed loop is provided.

9. An electromechanical sub-assembly according to claim 8, characterized in that the closed loop is arranged in the
35 circuit arrangement (2.2) of the control module (2).

10. An electromechanical sub-assembly according to one of the preceding claims, characterized in that the control module (2), the mechanical module (4) and the support module (3) in their assembled state form a housing which is
5 waterproof towards the periphery.

11. An electromechanical sub-assembly according to one of the preceding claims, characterized in that at least one
10 of the connection devices (3.3) forms an external terminal (3.3) of the electromechanical sub-assembly (1).

12. An electromechanical sub-assembly according to one of the preceding claims, characterized in that the
15 terminals (3.1, 3.2) and contacts (2.1, 4.1) each form a terminal block (3.1, 3.2) or a contact block (2.1, 4.1), respectively.